

CILT13D1G 2.8 - 12mm DC auto iris varifocal lens

Features


- 620 lines of resolution
- Amplify existing light with no distance limitations
- Minimum illumination 0.00001 lux (Intense Light @ 256x)
- Day & night camera without using IR LEDs
- Chameleon Cover™ - snaps on and can be painted to match any décor!
- 3-axis wall or ceiling mount
- Full OSD operation
- Vandal resistant
- Tamper resistant
- Weather resistant operation
- IP65 compliant

Specifications

Image Sensor	1/3" Sony Super-HAD II™ CCD
Resolution	620 TV lines
Minimum Illumination	0.00001 lux (intense light x256)
Total Pixels	811 (H) x 508 (V)
Effective Pixels	768 (H) x 494 (V)
Scanning System	2:1 interlace
Synchronization	Internal
OSD	Available
Backlight Compensation	BLC / HLC / D-WDR
S/N (Y signal)	52dB (AGC Off, Weight On)
White Balance	ATW / Manual / Set
Electronic Shutter Speed	Auto: (1/60 sec. - 1/100,000 sec.)
Sense-Up	Off / Auto (selectable limit x2 - x256)
Gain Control	High / Middle / Low / Off
3D-DNR	Auto / High / Middle / Low / Off



Camera shown with snap-on Chameleon™ Cover



Motion Detection	On / Off (4 zone)
Privacy	On / Off (8 zone)
Mirror	Off / Mirror / V-Flip / Rotate
Sharpness	0 - 30 (level adjustable)
Day & Night	Color / BW / Auto / Ext
Power Supply	12VDC (power supply not included)
Power Consumption	200mA
Operating Temperature/ Humidity	-4° F - 122° F / RH 90% max.
Dimensions	3.07" (H) x 4.33" (D)
Weight	1.54 lbs.

Optional Accessory



Speco Technologies is constantly developing and improving products.
We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 5/30/12