

H.264 Multi-Channel Digital Video Recorder

D4RS	4 Channel
D8RS	8 Channel
D16RS	16 Channel


D4RS250	D8RS250	D16RS250
D4RS500	D8RS500	D16RS500
D4RS1TB	D8RS1TB	D16RS1TB
	D8RS2TB	D16RS2TB

Features

- 4 / 8 / 16 Channel Digital Video Recorder
- Networkable DVR with free DDNS server
- Easy and simple graphical user interface
- EZCopy, EZRecord and EZSearch
- Programmable recording on motion detection, sensor, schedule, continuous and manual
- Recording rate at 120FPS at D1
- H.264 Video compression
- Built in S.M.A.R.T. Technology (Self-Monitoring, Analysis and Reporting, Technology for HDD)
- 4 Channel audio recording
- Covert camera operation provides enhanced security and administrator control
- Password to secure installation authorization
- Easy firmware upgrade by USB port or network
- Instant and convenient backup via USB Flash Drive or Network
- Simultaneous playback/record while continuing to network transfer or backup



For the latest mobile apps and CMS software go to: www.specotech.com/DVRApps



- User Access: up to 4 concurrent users
- Remote monitoring / recording / playback / configuration / software upgrades and PTZ control via Internet
- Network accessible via SpecoTech Multi-Client Software, Internet Explorer Web-Viewer and Speco Player Mobile Viewer
- PC and MAC® compatible
- Digital watermarking
- 3 year warranty
- Free Apps with support for View on iPhone®, iPad® or Android™

Specifications


120FPS @ 704 x 480 (D1)
 1 Internal hard drive
 H.264 video compression
 4 Channel audio input, 1 Channel audio output
 Motion detection, sensor, schedule, continuous and manual recording
 Video Outputs: 1 VGA, 1 BNC, 1 SPOT
 USB 2.0 port for snapshot and video clip exporting
 Multiple language on-screen menus
 IR remote control included
 Password to secure installation authorization
 Network software supports Static IP, DHCP and DDNS
 Network hardware supports 10/100/1000Mbps

Power Requirement: 12VDC @ 3A (D4RS),
 12VDC @ 5A (D8RS & D16RS)
 Operating Temperature: 41° F - 104° F
 Dimensions: 13.4" (W) x 2.48" (H) x 10.31" (D)
 Weight: 3.3 lbs.

Optional Accessory



ERS1V
Vented Rack Shelf



Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 2/22/12

D4/D8/D16RS Technical Specifications: H.264 Multi-Channel Channel Digital Video Recorder



ITEM		D4RS	D8RS	D16RS	
Video	Input	Channel	4	8	16
		Input Level	Composite, 1.0Vp-p, 75ohm		
		Signal Format	NTSC/PAL		
		Video Loss Check	Yes		
	Output	VGA	1 VGA (1280x1024, 1024x768)		
		BNC	Selectable	1 Channel	
SPOT		1 Channel			
Audio	Input & Output		4 Line input & 1 Line output		
	Audio Codec		G.711 (ADPCM)		
Alarm	Sensor Input (NC/NO Selectable)		4ch (NC/NO Selectable)		
	Alarm Output		1 Alarm out by Sensor, Motion and Video Loss		
Record	Compression		H.264		
	Multi-operation		QUADPLEX (Playback/Record/Network/Backup)		
	Resolution	D1	120fps	120fps	120fps
		Half D1	120fps	240fps	240fps
		CIF	120fps	240fps	480fps
	Recording quality grade		LEVEL1 (L) ~ LEVEL5 (H)		
	Recording Mode		Continuous / Schedule / Motion / Sensor / Manual		
	Motion Detection		Motion detection setup by Grid		
	Recording by channel's Resolution		Yes		
	Pre Recording		1 fps for 15 seconds to 20 minutes before an event		
Post Recording		10 seconds to 60 seconds after an event			
Display	Frame Rate (/Sec)		NTSC: 30fps/ch, 60 fields / PAL: 25fps/ch, 50 fields		
Playback	Multi-Decoding		1, 4	1, 4, 8	1, 4, 8, 16
	Search Mode		Timeline, Event, Archive, Log		
Storage	HDD	Interface Type	Serial ATA		
		Capacity of 1 HDD	1 TB	2 TB	
		Internal HDD Number	1		
	ESATA		-	1	
	Backup	USB Flash drive		Video & Still Image	
		USB External HDD		Video & Still Image	
		Network		Video & Still Image	
USB Port		2 (Front 1, Rear 1)			
User I/F	Menu Display		GUI		
	Input Method		Mouse, IR Remote control		
RS-485	PTZ control		1 RS-485		
Network	Dynamic DNS		Yes (Free DDNS)		
	Network Interface		10/100 base-TX Ethernet	10/100/1000 base-TX Ethernet	
	Network Streaming		CIF 15fps/channel max.		
Network Access	Web viewer (1:1)		Live, Search, Backup, PTZF, Remote Setup		
	3G Mobile Viewer (1:1)		Live, Search, PTZF		
	Multi-sites Monitoring SW (1:n)		Live, Search, Backup, PTZF, Remote Setup		
Features	DLS (Day Light Saving)		Yes		
	EZRecord		Yes		
	EZCopy		Yes		
	S.M.A.R.T.		Yes		
	Internal Beep		By Video Loss, HDD Error and S.M.A.R.T.		
	Multi Language		Yes (English, Spanish, French)		
	S/W Upgrade		USB Flash drive, Remote Network		
NTP		Yes			
Power	Power Supply Voltage		DC 12V 3A	DC 12V 5A	
Allowable operation temperature		41° F - 104° F, During storage: 14° F - 122° F			
Allowable operation humidity		20 - 80 %			
Weight	RS Unit Weight (Gross weight)		3.3lbs. (6.6lbs.)		
Dimension	RS Unit Dimension (W x H x D)		13.4" x 2.48" x 10.31"		

Please note that specifications and unit exterior design are subject to change without notification.

For more information contact Speco Technologies 200 New Highway, Amityville, NY 11701 Rev. 2/22/12
Toll Free: 1-800-645-5516 Fax: 631-957-9142 or 631-957-3880 Website: www.specotech.com